



WB-CB-300-*

1/3 HP CHILL BOSS ICE BANK LINE CHILLER

* 1 = One Pump

REFRIGERATION: 1/3HP, R134a Condensing Unit
2000 BTU Output, 2380 BTU Heat of Rejection

NOTE: 12" clearance required on three sides for optimum air flow maintenance.

ELECTRICAL: **No Pump:** 115 Volt AC, 60 hZ, 1 phase, 8.9 Full Load Amps
Dedicated 15 Amp circuit is required
Maximum Fuse / HACR Breaker: 15 Amp
includes six-foot cord with NEMA 5-15P grounded plug

One Pump: 115 Volt AC, 60 hZ, 1 phase, 15.1 Full Load Amps
Dedicated 25 Amp circuit is required
Maximum Fuse / HACR Breaker: 25 Amp
Includes six foot cord with NEMA 5-20P grounded plug.

COOLING CIRCUITS: Four 24-foot long 1/4" ID, with 3/8" Barbed Inlet/Outlet Fittings.

DIMENSIONS: **Height:** 26"
Width: 26"
Depth: 15-1/4"

WEIGHT: **Operating:** 250#
Shipped: 225# (includes packaging)

ICE BANK CAPACITY: 6 U.S. Gallons of Tap Water

PERFORMANCE: Two, 12 ounce drinks per minute at less than 40° F, 180 twelve ounce continuous drinks until ice bank depletion (2160 ounces total)

MAXIMUM TUBING LENGTH: 6' Direct Draw,
50' with optional Add-A-Pump Kit, p/n WB-BB-PK

OPTIONS: 6" Adjustable Legs (up to 7") (p/n WB-BB-L)
Add-A-Pump Kit (p/n [WB-BB-GRP-115](#))



**WB-CB-300
(No Pump)**



Includes:
Six-foot long
cord with
NEMA 5-15P,
grounded plug.

WB-CB-300-1



Includes:
Six-foot long
cord with
NEMA 5-20P,
grounded plug.

